



Mechanical characteristics
cables

interface dimensions acc. to assembly code

Components
centre contact
outer contact
crimp ferrule
insulator

Environmental
RoHS compliant

Mechanische Eigenschaften
Kabel

Steckgesicht nach Montageanleitung

Bauteile
Innenkontakt
Außenkontakt
Crimprohr
Isolierung

Umgebung
RoHS konform

Ⓐ G 1 : 7806A Belden; 9907 Belden; CNT-195; HPF 195 Harbour Industries; KX 15; LMR-195 TMS; RG-58C/U; WCX195
IEC 60169-17
A0805

Materials / Material
CuNi1Pb1P (C97)
CuZn39Pb3
Cu SF w
PE-LD

Ⓐ **Finish / Oberfläche**
NiP Au
Cu2Ni5
Ni5

Ⓐ 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight (g)
			gez./ drawn	10.06.2013	MA	
			gepr./ appr	21.06.2013	BJ	ca./approx.
			Maßstab/ scale	Benennung/ title		
			2:1	TNC Straight Jack TNC-Kabelbuchse		
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
Ⓐ	24867	10.06.2013	MA	K	J01011A2265	 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1
				Ersatz für/ replaces	Zeichnung vom 19.03.1998	