

Mechanical characteristics

interface dimensions acc. to mating life
coupling torque

Components

centre contact
outer contact
other metal parts
insulator

Electrical characteristics

impedance
frequency
return loss
working voltage
voltage proof
insulation resistance
contact resistance
centre contact
outer contact

Environmental

operating temp.
RoHS compliant

Mechanische Eigenschaften

Steckgesicht nach Steckzyklen
Kupplungsdrehmoment

Bauteile

Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Rückflussdämpfung
Betriebsspannung
Prüfspannung
Isolationswiderstand
Durchgangswiderstand
Innenkontakt
Außenkontakt

Umgebung

Betriebstemperatur
RoHS konform

① IEC 61169-16 (N), IEC 60169-15 (SMA)
>1000
N: 4-6 Nm; SMA: 79-113 Ncm

Materials / Material



CuBe2Pb
stainless steel / Edelstahl
stainless steel / Edelstahl
PTFE

Finish / Oberfläche


NiP-Au ②
passivated / passiviert
passivated / passiviert

50 Ω
0-18 GHz
① typ.: 2 GHz-40 dB; 11 GHz-28 dB; 18 GHz-20 dB
≤ 335 V_{eff} / 50 Hz
1 kV_{eff} / 50 Hz
≥ 5 MΩ
≤ 3 mΩ
≤ 2 mΩ

-40°C / +85°C
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]		
			gez./ drawn	17.11.2010	VM			
			gepr./ appr.	09.12.2010	KL	ca./approx. 19,22		
b a	28473	16.02.2017	MA	Maßstab/ scale	Benennung/ title			
	22935	01.06.2011	MA	2:1	Testadaptor N-SMA (f-f) Messadapter N-SMA (f-f)			
				untol. Maße/ dim. without tolerances according to	Unterf./doc. type	Zeichnungsnr./ drawing no.	 Maße/ dimensions: mm	
				K	J01027T0017			
				Ersatz für/ replaces	EWB00094-40 (ähnlich)			
							Original : DIN A4	
							Blatt/ sheet 1 von/ of 1	

 **Telegärtner**

 Maße/ dimensions: mm

Original : DIN A4

Blatt/ sheet 1 von/ of 1