

# Carbontex Washer Sizes

Washer Number	Outside Diameter		Inside Diameter		Thickness	
	Millimeters	Inches	Millimeter	Inches	Millimeter	Inches
	1	16	0.613	8.25	0.325	.5, .76 1
2	16.80	0.660	4.30	0.169	1	0.040
3	16.95	0.666	5.95	0.235	1	0.040
3A	16.95	0.666	9.92	0.390	0.65	0.020
4	17.15	0.675	9.35	0.368	0.5	0.025
5	17.80	0.700	10.35	0.407	0.76	0.030
6	18.25	0.720	8.35	0.330	1	0.040
7	18.75	0.735	10.90	0.430	1	0.040
7A	19	0.748	5.75	0.226	0.5	0.020
8	19.50	0.765	4.20	0.165	1	0.040
8A	20.18	0.794	4.93	0.195	0.65	0.025
9	20.50	0.805	10.85	0.430	0.76	0.030
10	20.50	0.810	8.10	0.320	0.5	0.020
11	20.65	0.810	8.90	0.350	1	0.040
12	20.70	0.815	13.15	0.518	0.76	0.030
12A	20.85	0.820	12.85	0.505	0.65	0.025
12B	21.11	0.831	14.75	0.580	0.65	0.025
13	21.28	0.840	5.18	0.205	1	0.040
13B	21.35	0.841	11.54	0.454	0.65	0.025
14	21.50	0.850	8.10	0.320	.76 or 1	.030 or .040
15	21.60	0.850	10.60	0.415	0.76	0.030
15A	22.35	0.880	11.64	0.458	0.65	0.025
16	22.60	0.890	12.70	0.500	1	0.040
16A	22.70	0.893	5.40	0.213	0.76	0.030
16B	22.70	0.893	12.69	0.499	0.76	0.030
17	22.95	0.905	8.30	0.325	1	0.040
18	22.98	0.095	8.15	0.320	.5 or .76	.020 or .030
19	23.90	0.940	11.30	0.445	1	0.040
20	24.15	0.950	14.50	0.572	1	0.040
21	24.55	0.965	10.60	0.415	.5 or .76	.020 or .030
21A	24.58	0.967	8.15	0.321	0.5	0.020
22	24.60	0.970	14.50	0.570	0.76	0.030
23	24.63	0.969	5.00	0.198	1	0.040
24	24.65	0.970	19.30	0.760	0.76	0.030
25	25.30	0.995	17.05	0.675	1	0.040
26	25.40	1.00	8.40	0.330	.76 or 1	.030 or .040
27	25.50	1	8.65	0.340	0.5	0.020
28	25.80	1.015	18.70	0.735	1	0.040
29	25.80	1.015	10.75	0.425	2	0.080
29A	25.95	1.020	16.17	0.636	0.5	0.020
30	25.95	1.020	19.25	0.760	1	0.040
31	26	1.022	12	0.475	0.76	0.030
31A	26.02	1.024	9.63	0.375	.65 or 1	.025 or .040
32	26.45	1.044	8.35	0.329	1	0.040
33	26.50	1.045	13	0.515	0.76	0.030
34	26.55	1.045	15.65	0.615	0.76	0.030
35	26.75	1.050	17	0.670	1	0.040
36	26.80	1.055	12.75	0.500	0.5	0.020
37	26.80	1.055	9.60	0.375	0.5	0.020
38	26.85	1.055	12.65	0.500	1	0.040
39	27.05	1.065	8.30	0.325	.5 or 1	.020 or .040
40	27.10	1.066	13.85	0.545	1 or 1.13	.040 or .044
41	27.95	1.100	15.65	0.615	0.76	0.030
42	28	1.100	10.90	0.430	0.76	0.030
43	28.35	1.115	18.90	0.745	1	0.040
44	28.60	1.125	10.90	0.429	0.76	0.030
45	28.65	1.127	21.05	0.830	1	0.040
45A	28.67	1.128	15.92	0.627	1.10 or .65	.043 or .025
45B	28.87	1.136	14.46	0.569	0.76	0.030
45C	28.70	1.130	11.80	0.465	0.5	0.020
46	29	1.140	8.60	0.340	0.76	0.030
47	30.95	1.220	21.60	0.850	0.76	0.030
48	31	1.22	8.90	0.35	1	0.040
49	31.15	1.225	17	0.668	1	0.040
50	32.35	1.275	8.25	0.325	.76 or .65	.030 or .025
51	32.50	1.280	18.06	0.709	1	0.040
52	32.65	1.285	17.10	0.673	0.76	0.030
53	33.50	1.320	18.05	0.710	1	0.040
54	33.80	1.330	9.50	0.373	1	0.040
55	34.65	1.365	19.45	0.765	0.76	0.030
56	34.92	1.376	20.26	0.807	0.96	0.037
57	35.07	1.376	15.50	0.611	1	0.040
58	35.50	1.400	17.20	0.677	1	0.040
59	35.60	1.400	8.70	0.340	0.5	0.020
60	38.15	1.500	14	0.550	1	0.040
61	38.50	1.515	24.10	0.948	1	0.040
62	40.45	1.590	21.05	0.830	0.76	0.030
63	40.45	1.590	13.00	0.510	0.76	0.030
64	41.05	1.620	16.35	0.645	0.76	0.030
65	41.05	1.620	12.55	0.495	0.76	0.030
66	41.05	1.620	10.10	0.400	0.76	0.030
67	43	1.695	16.25	0.640	0.76	0.030
68	43	1.695	12.15	0.480	0.76	0.030
69	43	1.695	10.35	0.405	0.76	0.030
70	49.15	1.935	20.35	0.800	1.16	0.045
71	55	2.165	20.05	0.790	1.16	0.045