

BST.



TECHNICAL SPECS

RAPID TEK FRONT WHEEL

SPECS



SIZES
3.5" x 17"



WEIGHT
6.06 lbs / 2.75 kg



MATERIALS
Wheels: Pre-preg carbon fibre
Hubs: 6082 T6 Aluminium



VALVE STEM
BST Ultra-High-Speed 90°
aluminium stem and cap



COMPLIANCE
DOT E and JWL compliant
for street and track use



WARRANTY
2 Year Factory Warranty

TESTS



**RADIAL IMPACT LOAD
(JASO T203-85)**
855 lbs / 388 kg



CORNERING FATIGUE LOAD
577 Nm



STATIC LOAD RATING
341 lbs / 155 kg



TORSION FATIGUE LOAD
543.9 Nm

FULLY COMPLIANT WITH ISO, JWL, and DOT E



BST.



TECHNICAL SPECS

RAPID TEK CONVENTIONAL REAR WHEEL

SPECS



SIZES

5.5" x 17"
6.0" x 17"



WEIGHT

7.05 lbs / 3.20 kg



MATERIALS

Wheels: Pre-preg carbon fibre
Hubs: 6082 T6 Aluminium



VALVE STEM

BST Ultra-High-Speed 90°
aluminium stem and cap



COMPLIANCE

DOT E and JWL compliant
for street and track use



WARRANTY

2 Year Factory Warranty

TESTS



**RADIAL IMPACT LOAD
(JASO T203-85)**

994 lbs / 451 kg



CORNERING FATIGUE LOAD

772 Nm



STATIC LOAD RATING

617 lbs / 280 kg



TORSION FATIGUE LOAD

1 030 Nm

FULLY COMPLIANT WITH ISO, JWL, and DOT E





TECHNICAL SPECS

RAPID TEK OFFSET REAR WHEEL

SPECS



SIZES

5.5" x 17"
6.0" x 17"
8.5" x 17"



WEIGHT

5.51 lbs / 2.50 kg



MATERIALS

Wheels: Pre-preg carbon fibre
Hubs: 6082 T6 Aluminium



VALVE STEM

BST Ultra-High-Speed 90°
aluminium stem and cap



COMPLIANCE

DOT E and JWL compliant
for street and track use



WARRANTY

2 Year Factory Warranty

TESTS



RADIAL IMPACT LOAD (JASO T203-85)

926 lbs / 420 kg



CORNERING FATIGUE LOAD

760 Nm



STATIC LOAD RATING

617 lbs / 280 kg



TORSION FATIGUE LOAD

1 030 Nm

FULLY COMPLIANT WITH ISO, JWL, and DOT E

