

ULV Cold Fogger electrically driven U260 / U120 U240 / U110

Airofog professional cold foggers U260 / U120 and U240 / U110 are portable ULV applicators powered from a 240/120 Volt AC electric supply. A reliable and powerful electric high speed (35,000 rpm) AC induction motor and fan create very small spray droplets, in the 15-30um droplet size range, by using a vortical air shear nozzle. The fine aerosol droplets will remain airborne for an extended period of time and are dispersed over an extensive area by the powerful air outlet at the nozzle.

The U260 / U120 model has an extendable hose that allows the operator to direct the fog into difficult to reach areas and spot treat where necessary.

	U260	U120	U240	U110
Electric Motor	220-240 V, 800 W	110-120 V, 700 W	220-240 V, 800 W	110-120 V, 700 W
Color	red		blue	
Solution Tank	HDPE, UV-light resistant, 5 litres with side filling			
Spray Nozzle	double turbine type			
Flow Rate Varible	0-400 ml/min.		0-150 ml/min.	
Flow Control	variable rotary control			
	5-position dosage control on request		not applicable	
Air Velocity	130 m/s			
Fogging Distance	12 m			
Shoulder Strap	double woven heavy-duty, 5 cm wide			
Flexible Hose	standard 50 cm, other length on request		not applicable	
Net Weight	3.4 kg		3.1 kg	
Dimensions	Ø28 x H40 cm			

<sup>\*</sup> Specifications are subject to change without notice or liability.

