



HBL9308 -- Receptacle

Product Specifications

Product Type	 <p>Flush Receptacles</p>
Receptacle Style	Single
Face Shape	Traditional
Standard	NEMA
Amperage	30A
Voltage	125V
Poles and Wires	2 Pole, 3 Wire Grounding
Wiring Method	Back and Side
Hospital Grade ?	No
Receptacle Grade	Heavy Duty Spec Grade
Face Style	Finder Groove
Color	 <p>Black</p>
NEMA No.	5-30R
Horsepower	2
Description	Heavy Duty Straight Blade Single Receptacle
Type	2 Pole, 3 Wire, Grounding
Rating	30A, 125V
Certification	UL, CSA, Fed Spec

Terminal Screw Material	Plated Steel
Ground Screw Material	Plated Steel
Top Material	Phenolic
Base Material	Phenolic
Power Contacts Material	brass
Mounting Strap Material	.062" (1.5) Plated Steel
Mounting Screw Material	Steel-Zinc Plated
Box Terminals Material	Brass
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#10-#4 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 V0.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
M Drawings	Click here for M-Drawing
UPC Number	78358501521
Weight in LBs	0.45