



The Power Cord Manufacturer  
www.stayonline.com

## Hubbell Straight Blade Devices

30A, 3-Phase 120/208V, 4 Pole, 4 Wire

### Non-Grounding Plug

#### Features

- Catalog number, ratings and certifications molded in face of plug.
- Gripping ribs provide secure gripping area.
- Supertough nylon housing

#### Ordering Information

Description

Black and white nylon

Cord Diameter

.625" - 1.310"  
(15.9 - 33.3 mm)

Hubbell Number

HBL8331C

Stay Online Item # 9220

#### Listings

UL Listed to File No. E1706

Certified to CSA

#### Specifications

Housing

Blade Holder

Blades

Box Terminals

Cord Clamps

Supertough Nylon

Reinforced Thermoplastic Polyester

Brass

Copper Alloy

Reinforced Thermoplastic Polyester

#### Performance

##### Electrical

Current Interrupting

Dielectric Voltage

Certified for current interrupting at full rated current

Withstands 2,000V minimum

##### Mechanical

Terminal Accomodation

Terminal Identification

Product Identification

#12 AWG - #4 AWG Copper conductors only.

Terminals identified in accordance with UL 498 and CSA

Ratings are a permanent part of the device

##### Environmental

Flammability

Moisture Resistance

Operating Temperatures

UL 94 HB

IP20

Max Continuous 75°C; Min -40°C (w/o impact)

