


PC100 -- Pin and Sleeve Products



Closure Cap, 100A Pin and Sleeve Males

PC3430

Product Specifications

Product Type	 <p>Replacement Items</p>
Replacement Part	Plug Cover
For Use With	IEC Devices
Hinge Spring	Stainless Steel (300 series)
Assembly Screws	Stainless Steel (300 series)
Gaskets	Neoprene
Certification	UL Listed, CSA Certified
Dielectric Withstand Voltage	Withstands 3,000V AC
Max Working Voltage	600V AC RMS
Current Interrupting	Certified for current interrupting at full rated current.
Short Circuit Withstand	Suitable for use on a circuit capable of delivering not more than 10,000 RMS symmetrical amperes at the voltage rating of the receptacle.
Endurance	Mechanical: 10,000 cycles, Electrical: 6,000 cycles.
Impact Resistance	In accordance with UL746C
Terminal Identification	Terminals identified in accordance with North American and International conventions.
Product Identification	Identification and ratings are a part of the external label and molded into the receptacle mount.
Ingress Protection	IP67 Suitability
Flammability	UL94-5VA and V-0 classification.
Operating Temperatures	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact.
UV Resistance	All materials are UV Stabilized.
Certifications	UL Listed, CSA Certified.
Device Description	Cap assemblies provide watertight sealing to a disconnected male Pin and Sleeve plug or inlet. Manufactured out of the same tough nonmetallic material as the watertight Pin and Sleeve devices for corrosion and abuse resistance.
UPC Number	78358537100

Weight in LBS	0.45
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

