







Packing:
 1. Bulk Pack.
 2. Bundles of 5 or 10 Pieces.

| NO. | SPECIFICATION | QTY | REMARK |
|-----|---|--------|--------|
| 1 | PSE HVCTF 2.0/3C+H05VV-F 1.5/3C+SJT 15/3C BLACK | 1PC | |
| 2 | TER:97606BS-1 | 2PCS | |
| 3 | TER:97607BS-1 | 1PC | |
| 4 | YP-33 INNER BODY | 1PC | |
| 5 | YP-33 PVC PLASTIC:50P BLACK | 32g/PC | |
| 6 | YC-18 PVC PLASTIC:50P BLACK | 25g/PC | |
| 7 | YC-18 INNER BODY | 1PC | |
| 8 | YC-18 TER: | 3PCS | |
| 9 | LABEL:(40+30)*30mm | 1PC | |
| 10 | LABEL:55*15mm | 1PC | |

Yung Li Co., Ltd. H05VV-F 3G 1.5mm² <VDE>  ES0140750  SU01027-4002
 A004049 60227 IEC 53(RVV) 300/500V c(UL)us E241374 SJT 3/C 15AWG(1.65mm²) 105°C
 300V VW-1 <PS>E JET HVCTF 3X2.0mm²  -F-

| | | | | | | | | |
|---|-------------|------|------|------|--------------------|-------------------------|---|---|
| Tolerance >0±0.30 >1.0±0.50 >10.0±1.0 >20.0±2.0 Angle: ±1° | Approved | | Date | | StayOnline® | | | |
| | Checked | | Date | | | | | |
| | Drawn | | Date | | Customer | | | |
| | Cat. No. | | | | P/N. | PFC201.5/15/2.0E79HVCTF | | |
| | Drawing No. | 6669 | | Rev. | | Material | P.V.C | Unit |
| | | | | | Scale | |  |  |