



„Knoti“ developed especially as firewood bundles binding aid for tying down without knots. The binding material remains undamaged and reusable.



Attach Knoti to a rope :

Fold down one end of the rope and pull the loop through the Knoti.....

Place the loop over the pin, pull it backwards over it and tighten it firmly. ( See also video at [www.Zurrbind.de](http://www.Zurrbind.de))



The tie-down ring replaces the usual loop at the end of a rope!

(1+2) pull the loose end of the rope through the eyelet, strain the connection and hold the rope with a fingertip in the Knoti so that it does not slip back ....



(3) now place the end of the rope away from you with the other hand .....

turn the resulting rope arc to a half stitch....



(5) place it over the conical pin, press the half stitch firmly under the Knoti with your thumb (Fig. 6) and pull the end of the rope forwards .... Done! (Video under [www.zurrbind.de](http://www.zurrbind.de))



(7) To open simply pull the end of the rope even after a heavy load.



Attention: To open the connection, put the wood bundle with Knoti in the upper area so that the rope connection loses some tension (this is the case with dried wood anyway). Now pull the rope end in the same direction as when straining, i.e. exactly in the direction of the conical pin. If you pull skew to the side or if the tension is too high, the connection cannot be opened! Turn the bundle a little or pull out a log to the side!

For firewood bundles, the single binding as described in pos. 1-6 is sufficient. Please note that the bond only holds as long as a certain residual tension is applied to it. This means that if the rope is completely relieved of strain, the connection could open. If necessary, the rope end can also be fixed to prevent the connection from opening unintentionally.

Attention:

Do not use Knoti and a rope to secure loads, for climbing and for connections that could endanger objects or persons if opened unintentionally or suddenly. Take particular care that no objects or persons are in the danger zone when lifting or transporting a bundle tied with a rope and Knoti. Knoti and a rope are suitable for tying a bundle of wood of max. 1 ster (1Rm) firewood. If the bundle is transported hanging from the rope, this is done at one's own risk, as this load is not permitted for Knoti and the rope. The rope and Knoti can break if overloaded. Parts flying around could endanger people or damage property. The load on the rope and Knoti must not exceed half the specified breaking load. Do not reuse damaged ropes or Knoti. Avoid sharp edges to avoid damaging the rope and Knoti.

**Knoti and rope, like other tensioning straps, are only a lashing system and not a "hoist"/lifting tool.**

Always pay attention to your **Danger Area** and our **Safety instructions**

**We wish you much success and accident-free work!**