

DIATOP SUGIHARA Guide Bar

Solid Hard Nose Bar

(Hard Tip)

Professional quality solid hard nose bar
with Stellite (cobalt alloy) Tip.

Polished finish.



Replaceable Sprocket nose bar

(Star Tip)

Professional quality sprocket nose bar.
with High durability Sprocket.

Polished finish.



Laminated Sprocket nose bar


(Star Tip)

High quality sprocket nose bar.
with High durability Sprocket.

Painted finish.




STIHL




CHAIN SAW MODEL							Guide Bar Part Number					
			Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
	CM	Inch					Standard	Light	Standard	Light	Standard	Light
009,010,011	30	12	.050"	1/4"	64E	Carving R9	SL2A-0X30-A					
	35	14	.050"	1/4"	72E	Carving R9	SL2A-0X35-A					
017,018,019T	25	10	.050"	1/4"	60E	Carving R10		SL2C-0Z25-A				
020,020T,	30	12	.050"	1/4"	68E	Carving R10		SL2C-0Z30-A				
021,021C	30	12	.050"	1/4"	68E	Carving R12	SL2A-0Y30-A	SL2C-0Y30-A				
023,023/C,	35	14	.050"	1/4"	76E	Carving R12	SL2A-0Y35-A	SL2C-0Y35-A				
025, 025C	41	16	.050"	1/4"	86E	Carving R12	SL2A-0Y41-A	SL2C-0Y41-A				
MS170,180C	30	12	.050"	1/4"	68E	Narrow R15	SL2A-0R30-A	SL2C-0R30-A				
MS190,190T	35	14	.050"	1/4"	76E	Narrow R15	SL2A-0R35-A	SL2C-0R35-A				
MS191T, 192T	41	16	.050"	1/4"	86E	Narrow R15	SL2A-0R41-A	SL2C-0R41-A				
MS200,200T	30	12	.050"	1/4"	64E	R20	SL2A-0A30-A	SL2C-0A30-A				
MS210,230	35	14	.050"	1/4"	72E	R20	SL2A-0A35-A	SL2C-0A35-A				
MS241,250	40	16	.050"	1/4"	80E	R20	SL2A-0A40-A	SL2C-0A40-A				
MS250C	41	17	.050"	1/4"	86E	R20	SL2A-0A41-A	SL2C-0A41-A				
HT70, HT75												
E10, E14,	40	16	.043"	3/8"LP	55E							SL2M-4L40-A
E140, E160	30	12	.050"	3/8"LP	45E	R24	SL2A-0B30-A			SL2L-0L30-A	SL2M-0L30-A	
E180CQT,	35	14	.050"	3/8"LP	50E	R24	SL2A-0B35-A			SL2L-0L35-A	SL2M-0L35-A	
	40	16	.050"	3/8"LP	55E	R24	SL2A-0B40-A			SL2L-0L40-A	SL2M-0L40-A	
	45	18	.050"	3/8"LP	61E	R24	SL2A-0B45-A					
	40	16	.063"	.325"	62E	R25.3					SL2L-3J40-A	SL2M-3J40-A
	44	18	.063"	.325"	68E	R25.3						SL2M-3J44-A


STIHL




CHAIN SAW MODEL							Guide Bar Part Number							
	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar		Standard		Light		Standard		Light	
	cm	Inch	Gauge	Pitch	DL	Tip Feature	Standard	Light	Standard	Light	Standard	Light	Standard	Light
012,024,026,028	40	16	.063"	.325"	67E	25.5		SS2C-3B40-A						
030,031,032,034	40	16	.063"	.325"	67E	28.5	ST2A-3C40-A	ST2C-3C40-A	ST2T-3J40-A	ST2U-3J40-A	ST2L-3J40-A	ST2M-3J40-A		
036,038,039,040	45	18	.063"	.325"	74E	28.5	ST2A-3C45-A	ST2C-3C45-A	ST2T-3J45-A	ST2U-3J45-A	ST2L-3J45-A	ST2M-3J45-A		
041,042,044C,	50	20	.063"	.325"	81E	28.5	ST2A-3C50-A	ST2C-3C50-A	ST2T-3J50-A	ST2U-3J50-A	ST2L-3J50-A			
045,046C,048,	36	14	.063"	3/8"	56E				ST2T-3Q36-A		ST2L-3Q36-A			
056,064,066	40	16	.063"	3/8"	60E	35	ST2A-3D40-A	ST2C-3D40-A	ST2T-3Q40-A	ST2U-3Q40-A	ST2L-3Q40-A	ST2M-3Q40-A		
MS240,260,261	45	18	.063"	3/8"	66E	35	ST2A-3D45-A	ST2C-3D45-A	ST2T-3Q45-A	ST2U-3Q45-A	ST2L-3Q45-A	ST2M-3Q45-A		
MS270C	50	20	.063"	3/8"	72E	35	ST2A-3D50-A	ST2C-3D50-A	ST2T-3Q50-A	ST2U-3Q50-A	ST2L-3Q50-A			
MS280,280C	57	23	.063"	3/8"	78E	35	ST2A-3D57-A	ST2C-3D57-A	ST2T-3Q57-A	ST2U-3Q57-A				
MS290,310,360	63	25	.063"	3/8"	84E	35	ST2A-3D63-A	ST2C-3D63-A	ST2T-3Q63-A	ST2U-3Q63-A				
MS361,390,440	70	28	.063"	3/8"	92E	35	ST2A-3D70-A	ST2C-3D70-A	ST2T-3Q70-A	ST2U-3Q70-A				
MS460,650,660	74	29	.063"	3/8"	96E	35	ST2A-3D74-A							
MS460,650,660	76	30	.063"	3/8"	98E				ST2T-3Q76-A					
	80	32	.063"	3/8"	105E					ST2U-3Q80-A				
	90	36	.063"	3/8"	114E	35	ST2A-3D90-A	ST2C-3D90-A						
	41	16	.050"	1/4"	86E	Narrow R15	SQ2A-0R41-A	SQ2C-0R41-A						
07S,08,08S,	53	21	.063"	.404"	68E	43	SG6A-3E53-A		SG6T-3S53-A					
050,051,070	63	25	.063"	.404"	84E	43	SG6A-3E63-A		SG6T-3S63-A					
075,076,084,	75	30	.063"	.404"	92E	43	SG6A-3E75-A		SG6T-3S75-A					
088,090	83	33	.063"	.404"	100E	43	SG6A-3E83-A		SG6T-3S83-A					
MS880,E30	90	36	.063"	.404"	104E	43	SG6A-3E90-A		SG6T-3S90-A					

HUSQVARNA

CHAIN SAW MODEL							Guide Bar Part Number					
	CM	Inch	Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
							Standard	Light	Standard	Light	Standard	Light
61,P61,64,65 66,70,77 160,162,180 181,185,260 266,268,272 280,281,285, 288XP,298,362, 365,371,372, 380,385,394 395XP/XPG 480,1100 2100,2100XP 3120XP	43	17	.058"	3/8"	64E	R28.5	VT3A-8C43-A	VT3C-8C43-A				
	45	18	.058"	3/8"	68E	R28.5	VT3A-8C45-A	VT3C-8C45-A				
	40	16	.058"	3/8"	60E	R33	VT3A-8D40-A	VT3C-8D40-A	VT3T-8Q40-A	VT3U-8Q40-A	VT2L-8Q40-A	VT2M-8Q40-A
	43	17	.058"	3/8"	64E	R33	VT3A-8D43-A	VT3C-8D43-A	VT3T-8Q43-A	VT3U-8Q43-A	VT2L-8Q43-A	VT2M-8Q43-A
	45	18	.058"	3/8"	68E	R33	VT3A-8D45-A	VT3C-8D45-A	VT3T-8Q45-A	VT3U-8Q45-A	VT2L-8Q45-A	VT2M-8Q45-A
	50	20	.058"	3/8"	72E	R33	VT3A-8D50-A	VT3C-8D50-A	VT3T-8Q50-A	VT3U-8Q50-A	VT2L-8Q50-A	VT2M-8Q50-A
	55	22	.058"	3/8"	76E	R33	VT3A-8D55-A	VT3C-8D55-A	VT3T-8Q55-A	VT3U-8Q55-A		
	61	24	.058"	3/8"	82E	R33	VT3A-8D61-A	VT3C-8D61-A	VT3T-8Q61-A	VT3U-8Q61-A		
	62	25	.058"	3/8"	84E				VT3T-8Q62-A			
	70	28	.058"	3/8"	92E	R33	VT3A-8D70-A		VT3T-8Q70-A	VT3U-8Q70-A		
65,70,185,268, 288,395XP/G 371,1100,3120	60	24	.063"	.404"	76E	R36.5	VF2A-3E60-A		VF2T-3S60-A			
	70	28	.063"	.404"	84E	R36.5	VF2A-3E70-A		VF2T-3S70-A			
	75	30	.063"	.404"	90E	R36.5	VF2A-3E75-A		VF2T-3S75-A			
	85	34	.063"	.404"	102E	R36.5	VF2A-3E85-A		VF2T-3S85-A			
	100	40	.063"	.404"	116E	R36.5	VF2A-3E100-A		VF2T-3S100-A			
	105	42"	.063"	.404"	124E	R36.5	VF2A-3E105-A					




CHAIN SAW MODEL							Guide Bar Part Number							
	cm		Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar			
	Inch						Standard	Light	Standard	Light	Standard	Light		
G2500T,2550T G3100T G310,3200	30	12	.050"	1/4"	68E	Carving R9	BM2A-0X30-A							
	35	14	.050"	1/4"	76E	Carving R9	BM2A-0X35-A							
	20	8	.050"	1/4"	52E	Carving R10		UL6C-0Z20-A						
	25	10	.050"	1/4"	60E	Carving R10		UL6C-0Z25-A						
	30	12	.050"	1/4"	68E	Carving R10	UL6A-0Z30-A	UL6C-0Z30-A						
	35	14	.050"	1/4"	76E	Carving R10	BM2A-0Z35-A	BM2C-0Z35-A						
	30	12	.050"	1/4"	68E	Carving R12	BM2A-0Y30-A	BM2C-0Y30-A						
	35	14	.050"	1/4"	76E	Carving R12	BM2A-0Y35-A	BM2C-0Y35-A						
	30	12	.050"	1/4"	68E	Narrow R15	BM2A-0R30-A	BM2C-0R30-A						
	20	8	.050"	1/4"	52E								EM1M-0V20-A	
	25	10	.050"	1/4"	60E								EM1M-0V25-A	
	30	12	.050"	1/4"	68E							BL1L-0G30-A	BL1M-0G30-A	
		28	11	.050"	3/8"LP	45E						BL1L-0L28-A	BL1M-0L28-A	
		30	12	.050"	3/8"LP	47E						BL1L-0L30-A	BL1M-0L30-A	
	34	14	.050"	3/8"LP	52E						BL1L-0L34-A	BL1L-0L34-A		
	35	14	.050"	3/8"LP	58E						BL1L-0L35-A	BL1M-0L35-A		
G345,375,380	35	14	.050"	1/4"	76E	Carving R10	BM2A-0Z35-A	BM2C-0Z35-A						
	41	16	.050"	1/4"	86E	Carving R10	BM2A-0Z41-A	BM2C-0Z41-A						
	35	14	.050"	1/4"	76E	Carving R12	BM2A-0Y35-A	BM2C-0Y35-A						
	41	16	.050"	1/4"	86E	Carving R12	BM2A-0Y41-A	BM2C-0Y41-A						
	35	14	.050"	1/4"	76E	Narrow R15	BM2A-0R35-A	BM2C-0R35-A						
	41	16	.050"	1/4"	86E	Narrow R15	BM2A-0R41-A	BM2C-0R41-A						
	30	12	.050"	1/4"	68E	R18		BL1C-0T30-A						
	35	14	.050"	1/4"	76E	R18	BL1A-0T35-A	BL1C-0T35-A						
	41	16	.050"	1/4"	86E	R18	BL1A-0T41-A	BL1C-0T41-A						
	30	12	.050"	1/4"	68E	R18	BL1A-0A30-A							
	35	14	.050"	1/4"	76E	R20	BL1A-0A35-A	BL1C-0A35-A			BL1L-0G35-A	BL1M-0G35-A		
	40	16	.050"	1/4"	84E	R20	BL1A-0A40-A	BL1C-0A40-A			BL1L-0G40-A	BL1M-0G40-A		
	41	16	.050"	1/4"	86E	R20	BL1A-0A41-A	BL1C-0A41-A			BL1L-0G41-A	BL1M-0G41-A		
		30	12	.050"	3/8"LP	47E	R24.5	BL1A-0B30-A	BL1C-0B30-A			BL1L-0L30-A	BL1M-0L30-A	
		35	14	.050"	3/8"LP	53E	R24.5	BL1A-0B35-A	BL1C-0B35-A			BL1L-0L35-A	BL1M-0L35-A	
		38	16	.050"	3/8"LP	56E						BL1L-0L38-A	BL1M-0L38-A	
		39	16	.050"	3/8"LP	57E						BL1L-0L39-A	BL1M-0L39-A	
		40	16	.050"	3/8"LP	58E	R24.5	BL1A-0B40-A	BL1C-0B40-A			BL1L-0L40-A	BL1M-0L40-A	
		41	16	.050"	3/8"LP	60E							BL1M-0L41-A	
	43	17	.050"	3/8"LP	62E							BL1M-0L43-A		
	45	18	.050"	3/8"LP	64E							BL1M-0L45-A		




CHAIN SAW MODEL							Guide Bar Part Number						
	cm		Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar		
	Inch						Standard	Light	Standard	Light	Standard	Light	
G345,375,380 G415,4200	35	14	.050"	.325"	60E	Small Sprocket					BM3U-0H35-A	BM2L-0H35-A	BM2M-0H35-A
	37	15	.050"	.325"	64E	Small Sprocket					BM3U-0H37-A	BM2L-0H37-A	BM2M-0H37-A
	40	16	.050"	.325"	66E	Small Sprocket					BM3U-0H40-A	BM2L-0H40-A	BM2M-0H40-A
	42	17	.050"	.325"	68E	Small Sprocket					BM3U-0H42-A		BM2M-0H42-A
	45	18	.050"	.325"	72E	Small Sprocket						BM2L-0H45-A	BM2M-0H45-A
	37	15	.050"	.325"	64E						BM3U-0J37-A	BM2L-0J37-A	
	40	16	.050"	.325"	66E	R27		BM3C-0C40-A			BM3U-0J40-A	BM2L-0J40-A	BM2M-0J40-A
	42	17	.050"	.325"	68E						BM3U-0J42-A		
	45	18	.050"	.325"	72E	R27		BM3C-0C45-A			BM3U-0J45-A	BM2L-0J45-A	BM2M-0J45-A
	33	13	.050"	.325"	56E				BM3T-8J33-A				
	35	14	.058"	.325"	60E	Small SP						BM2L-8H35-A	BM2M-8H35-A
	37	15	.058"	.325"	64E	Small SP						BM2L-8H37-A	BM2M-8H37-A
	40	16	.058"	.325"	66E	Small SP						BM2L-8H40-A	BM2M-8H40-A
	42	17	.058"	.325"	68E	Small SP						BM2L-8H42-A	BM2M-8H42-A
	45	18	.058"	.325"	72E	Small SP						BM2L-8H45-A	BM2M-8H45-A
	35	14	.058"	.325"	60E	R24.5		BM3C-8B35-A			BM3U-8J35-A		BM2M-8J35-A
	37	15	.058"	.325"	64E	R24.5	BM3A-8B37-A	BM3C-8B37-A	BM3T-8J37-A	BM3U-8J37-A	BM2L-8J37-A	BM2M-8J37-A	
	40	16	.058"	.325"	66E	R24.5	BM3A-8B40-A	BM3C-8B40-A	BM3T-8J40-A	BM3U-8J40-A	BM2L-8J40-A	BM2M-8J40-A	
	40	16	.058"	.325"	66E	R27	BM3A-8C40-A						
42	17	.058"	.325"	68E	R27	BM3A-8C42-A	BM3C-8C42-A	BM3T-8J42-A	BM3U-8J42-A	BM2L-8J42-A	BM2M-8J42-A		
45	18	.058"	.325"	72E	R27	BX3A-8C45-A	BX3C-8C45-A	BX3T-8J45-A	BX3U-8J45-A	BM2L-8J45-A	BM2M-8J45-A		
G451,500 G4500,G5000	40	16	.058"	.325"	66E	R27	BC3A-8C40-A	BC3C-8C40-A	BC3T-8J40-A	BC3U-8J40-A	BM2L-8J40-A	BM2M-8J40-A	
	45	18	.058"	.325"	72E	R27	BC3A-8C45-A	BC3C-8C45-A	BC3T-8J45-A	BC3U-8J45-A	BM2L-8J45-A	BM2M-8J45-A	
	47	19	.058"	.325"	76E	R27	BC3A-8C47-A	BC3C-8C47-A	BC3T-8J47-A	BC3U-8J47-A	BM2L-8J47-A	BM2M-8J47-A	
	50	20	.058"	.325"	80E	R27	BC3A-8C50-A	BC3C-8C50-A	BC3T-8J50-A	BC3U-8J50-A	BM2L-8J50-A	BM2M-8J50-A	
	55	22	.058"	.325"	84E	R27	BC3A-8C55-A	BC3C-8C55-A	BC3T-8J55-A	BC3U-8J55-A			
	60	24	.058"	.325"	88E	R27	BC3A-8C60-A	BC3C-8C60-A	BC3T-8J60-A	BC3U-8J60-A			
G621	40	16	.058"	3/8"	60E	R27.5	XT2A-8C40-A	XT2C-8C40-A	XT2T-8Q40-A	XT2U-8Q40-A	XT2L-8Q40-A	XT2M-8Q40-A	
	45	18	.058"	3/8"	66E	R27.5	XT2A-8C45-A	XT2C-8C45-A	XT2T-8Q45-A	XT2U-8Q45-A	XT2L-8Q45-A	XT2M-8Q45-A	
	50	20	.058"	3/8"	70E	R27.5	XT2A-8C50-A	XT2C-8C50-A	XT2T-8Q50-A	XT2U-8Q50-A	XT2L-8Q50-A	XT2M-8Q50-A	
	51	20	.058"	3/8"	72E	R27.5	XT2A-8C51-A	XT2C-8C51-A	XT2T-8Q51-A	XT2U-8Q51-A			
	61	24	.058"	3/8"	84E	R27.5	XT2A-8C61-A	XT2C-8C61-A	XT2T-8Q61-A	XT2U-8Q61-A			


ECHO(KIORITZ)

CHAIN SAW MODEL							Guide Bar Part Number						
	cm	Inch	Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar		
							Standard	Light	Standard	Light	Standard	Light	
CS280,285	30	12	.050"	1/4"	68E	Carving R9	BM2A-0X30-A						
CS290,300,	35	14	.050"	1/4"	76E	Carving R9	BM2A-0X35-A						
CS301,302	20	8	.050"	1/4"	52E	Carving R10		UL6C-0Z20-A					EM1M-0V20-A
CS304,315	25	10	.050"	1/4"	60E	Carving R10		UL6C-0Z25-A					EM1M-0V25-A
CS320,328	30	12	.050"	1/4"	68E	Carving R10	UL6A-0Z30-A	UL6C-0Z30-A					
CS330,340	35	14	.050"	1/4"	76E	Carving R10	BM2A-0Z35-A	BM2C-0Z35-A					
CS341,345	41	16	.050"	1/4"	86E	Carving R10	BM2A-0Z41-A	BM2C-0Z41-A					
CS346,351	30	12	.050"	1/4"	68E	Carving R12	BM2A-0Y30-A	BM2C-0Y30-A					
CS352,360	35	14	.050"	1/4"	76E	Carving R12	BM2A-0Y35-A	BM2C-0Y35-A					
CS2000	41	16	.050"	1/4"	86E	Carving R12	BM2A-0Y41-A	BM2C-0Y41-A					
CS2600,2700	30	12	.050"	1/4"	68E	Narrow R15	BM2A-0R30-A	BM2C-0R30-A			BL1L-0G30-A	BL1M-0G30-A	
CS2800,2900	35	14	.050"	1/4"	76E	Narrow R15	BM2A-0R35-A	BM2C-0R35-A					
CS3000,3050	41	16	.050"	1/4"	86E	Narrow R15	BM2A-0R41-A	BM2C-0R41-A					
CS3200,3400	30	12	.050"	1/4"	68E	R18		BL1C-0T30-A					
CS3450,3500	35	14	.050"	1/4"	76E	R18	BL1A-0T35-A	BL1C-0T35-A					
CS3600,3700	41	16	.050"	1/4"	86E	R18	BL1A-0T41-A	BL1C-0T41-A					
ECS150	35	14	.050"	1/4"	76E	R20	BL1A-0A35-A	BL1C-0A35-A			BL1L-0G35-A	BL1M-0G35-A	
	40	16	.050"	1/4"	84E	R20	BL1A-0A40-A	BL1C-0A40-A			BL1L-0G40-A	BL1M-0G40-A	
	41	16	.050"	1/4"	86E	R20	BL1A-0A41-A	BL1C-0A41-A			BL1L-0G41-A	BL1M-0G41-A	
	28	11	.050"	3/8"LP	45E						BL1L-0L28-A	BL1M-0L28-A	
	30	12	.050"	3/8"LP	47E	R24.5	BL1A-0B30-A						
	34	14	.050"	3/8"LP	52E						BL1L-0L34-A	BL1M-0L34-A	
	35	14	.050"	3/8"LP	53E	R24.5	BL1A-0B35-A	BL1C-0B35-A			BL1L-0L35-A	BL1M-0L35-A	
	38	16	.050"	3/8"LP	56E						BL1L-0L38-A	BL1M-0L38-A	
	39	16	.050"	3/8"LP	57E						BL1L-0L39-A	BL1M-0L39-A	
	40	16	.050"	3/8"LP	58E	R24.5	BL1A-0B40-A	BL1C-0B40-A			BL1L-0L40-A	BL1M-0L40-A	
	41	16	.050"	3/8"LP	60E							BL1M-0L41-A	
	43	17	.050"	3/8"LP	62E							BL1M-0L43-A	


ECHO(KIORITZ)




CHAIN SAW MODEL							Guide Bar Part Number					
							Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
	cm	Inch	Gauge	Pitch	DL	Tip Feature	Standard	Light	Standard	Light	Standard	Light
CS3900,4000 CS4010,4200 CS4400,4500 CS4510,4600 CS4610,5000	37	15	.058"	.325"	64E	R24.5	BM3A-8B37-A	BM3C-8B37-A	BM3T-8J37-A	BM3U-8J37-A	BM2L-8J37-A	BM2M-8J37-A
	40	16	.058"	.325"	66E	R27	BM3A-8C40-A	BM3C-8C40-A	BM3T-8J40-A	BM3U-8J40-A	BM2L-8J40-A	BM2M-8J40-A
	42	17	.058"	.325"	68E	R27	BM3A-8C42-A	BM3C-8C42-A	BM3T-8J42-A	BM3U-8J42-A	BM2L-8J40-A	BM2M-8J40-A
	45	18	.058"	.325"	72E	R27	BX3A-8C45-A	BX3C-8C45-A	BX3T-8J45-A	BX3U-8J45-A	BM2L-8J45-A	BM2M-8J45-A
	50	20	.058"	.325"	80E	R27	BX3A-8C50-A	BX3C-8C50-A	BX3T-8J50-A	BX3U-8J50-A	BM2L-8J50-A	BM2M-8J50-A
	55	22	.058"	.325"	84E	R27	BX3A-8C55-A	BX3C-8C55-A	BX3T-8J55-A	BX3U-8J55-A		
CS680, 800 CS5501, 6700 CS6701, 8000	40	16	.058"	3/8"	60E	R27.5	XT2A-8C40-A	XT2C-8C40-A	XT2T-8Q40-A	XT2U-8Q40-A	XT2L-8Q40-A	XT2M-8Q40-A
	43	17	.058"	3/8"	64E				XT2T-8Q43-A			
	45	18	.058"	3/8"	66E	R27.5	XT2A-8C45-A	XT2C-8C45-A	XT2T-8Q45-A	XT2U-8Q45-A	XT2L-8Q45-A	XT2M-8Q45-A
	50	20	.058"	3/8"	70E	R27.5	XT2A-8C50-A	XT2C-8C50-A	XT2T-8Q50-A	XT2U-8Q50-A	XT2L-8Q50-A	XT2M-8Q50-A
	51	21	.058"	3/8"	72E	R27.5	XT2A-8C51-A	XT2C-8C51-A	XT2T-8Q51-A	XT2U-8Q51-A		
	61	24	.058"	3/8"	84E	R27.5	XT2A-8C61-A	XT2C-8C61-A	XT2T-8Q61-A	XT2U-8Q61-A	XT2L-8Q61-A	

CHAIN SAW MODEL							Guide Bar Part Number					
	cm	Inch	Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
							Standard	Light	Standard	Light	Standard	Light
E400,440,488 E580,685,757 E1045	42	17	.058"	.325"	68E	R27	BQ4A-8C42-A	BQ4C-8C42-A	BQ4T-8J42-A	BQ4U-8J42-A		
	45	18	.058"	.325"	72E	R27	BQ4A-8C45-A	BQ4C-8C45-A	BQ4T-8J45-A	BQ4U-8J45-A		
	47	19	.058"	.325"	76E	R27	BQ4A-8C47-A	BQ4C-8C47-A	BQ4T-8J47-A	BQ4U-8J47-A		
	50	21	.058"	.325"	80E	R27	BQ4A-8C50-A	BQ4C-8C50-A	BQ4T-8J50-A	BQ4U-8J50-A		
	53	21	.058"	.325"	84E	R27	BQ4A-8C53-A	BQ4C-8C53-A	BQ4T-8J53-A	BQ4U-8J53-A		
	43	17	.058"	3/8"	64E	R28.5	VT3A-8C43-A	VT3C-8C43-A				
	45	18	.058"	3/8"	68E	R28.5	VT3A-8C45-A	VT3C-8C45-A				
	40	16	.058"	3/8"	60E	R33	VT3A-8D40-A	VT3C-8D40-A	VT3T-8Q40-A	VT3U-8Q40-A	VT2L-8Q40-A	VT2M-8Q40-A
	43	17	.058"	3/8"	64E	R33	VT3A-8D43-A	VT3C-8D43-A	VT3T-8Q43-A	VT3U-8Q43-A	VT2L-8Q43-A	VT2M-8Q43-A
	45	18	.058"	3/8"	68E	R33	VT3A-8D45-A	VT3C-8D45-A	VT3T-8Q45-A	VT3U-8Q45-A	VT2L-8Q45-A	VT2M-8Q45-A
	50	20	.058"	3/8"	72E	R33	VT3A-8D50-A	VT3C-8D50-A	VT3T-8Q50-A	VT3U-8Q50-A	VT2L-8Q50-A	VT2M-8Q50-A
	55	22	.058"	3/8"	76E	R33	VT3A-8D55-A	VT3C-8D55-A	VT3T-8Q55-A	VT3U-8Q55-A		
	61	24	.058"	3/8"	82E	R33	VT3A-8D61-A	VT3C-8D61-A	VT3T-8Q61-A	VT3U-8Q61-A		
	62	25	.058"	3/8"	84E				VT3T-8Q62-A			
	70	28	.058"	3/8"	92E	R33	VT3A-8D70-A		VT3T-8Q70-A	VT3U-8Q70-A		

DOLMAR


CHAIN SAW MODEL							Guide Bar Part Number					
	CM	Inch	Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
							Standard	Light	Standard	Light	Standard	Light
ES152,162 PS3300,330 PS340,341,344 PS400,401 100,101,102 103,104,106 AS172,	30	12	.050"	1/4"	68E	Carving R9	BM2A-0X30-A					
	35	14	.050"	1/4"	76E	Carving R9	BM2A-0X35-A					
	20	8	.050"	1/4"	52E	Carving R10		UL6C-0Z20-A				EM1M-0V20-A
	25	10	.050"	1/4"	60E	Carving R10		UL6C-0Z25-A				EM1M-0V25-A
	30	12	.050"	1/4"	68E	Carving R10	UL6A-0Z30-A	UL6C-0Z30-A				
	30	12	.050"	1/4"	68E	Carving R10	BM2A-0Z30-A	BM2C-0Z30-A				
	35	14	.050"	1/4"	76E	Carving R10	BM2A-0Z35-A	BM2C-0Z35-A				
	41	16	.050"	1/4"	86E	Carving R10	BM2A-0Z41-A	BM2C-0Z41-A				
	30	12	.050"	1/4"	68E	Carving R12	BM2A-0Y30-A	BM2C-0Y30-A				
	35	14	.050"	1/4"	76E	Carving R12	BM2A-0Y35-A	BM2C-0Y35-A				
	41	16	.050"	1/4"	86E	Carving R12	BM2A-0Y41-A	BM2C-0Y41-A				
	30	12	.050"	1/4"	68E	Narrow R15	BM2A-0R30-A	BM2C-0R30-A			BL1L-0G30-A	BL1M-0G30-A
	35	14	.050"	1/4"	76E	Narrow R15	BM2A-0R35-A	BM2C-0R35-A				
	41	16	.050"	1/4"	86E	Narrow R15	BM2A-0R41-A	BM2C-0R41-A				
	35	14	.050"	1/4"	76E	R18	BL1A-0T35-A	BL1C-0T35-A				
	41	16	.050"	1/4"	86E	R18	BL1A-0T41-A	BL1C-0T41-A				
	35	14	.050"	1/4"	76E	R20	BL1A-0A35-A	BL1C-0A35-A			BL1L-0G35-A	BL1M-0G35-A
	40	16	.050"	1/4"	84E	R20	BL1A-0A40-A	BL1C-0A40-A			BL1L-0G40-A	BL1M-0G40-A
41	16	.050"	1/4"	86E	R20	BL1A-0A41-A	BL1C-0A41-A			BL1L-0G41-A	BL1M-0G41-A	

DOLMAR



CHAIN SAW MODEL							Guide Bar Part Number					
			Gauge	Pitch	DL	Tip Feature	Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
	cm	Inch					Standard	Light	Standard	Light	Standard	Light
ES152,162	28	11	.050"	3/8"LP	45E						BL1L-0L28-A	BL1M-0L28-A
PS3300,330	30	12	.050"	3/8"LP	47E	R24.5	BL1A-0B30-A	BL1C-0B30-A			BL1L-0L30-A	BL1M-0L30-A
PS340,341,344	34	14	.050"	3/8"LP	52E						BL1L-0L34-A	BL1M-0L34-A
PS400,401	35	14	.050"	3/8"LP	53E	R24.5	BL1A-0B35-A	BL1C-0B35-A			BL1L-0L35-A	BL1M-0L35-A
100,101,102	38	16	.050"	3/8"LP	56E						BL1L-0L38-A	BL1M-0L38-A
103,104,106	39	16	.050"	3/8"LP	57E						BL1L-0L39-A	BL1M-0L39-A
	40	16	.050"	3/8"LP	58E	R24.5	BL1A-0B40-A	BL1C-0B40-A			BL1L-0L40-A	BL1M-0L40-A
105,108,109	37	15	.058"	.325"	64E	R24.5	BM3A-8B37-A	BM3C-8B37-A	BM3T-8J37-A	BM3U-8J37-A	BM2L-8J37-A	BM2M-8J37-A
110,116	40	16	.058"	.325"	66E	R27	BM3A-8C40-A	BM3C-8C40-A	BM3T-8J40-A	BM3U-8J40-A	BM2L-8J40-A	BM2M-8J40-A
ES1800	42	17	.058"	.325"	68E	R27	BM3A-8C42-A	BM3C-8C42-A	BM3T-8J42-A	BM3U-8J42-A	BM2L-8J40-A	BM2M-8J40-A
	45	18	.058"	.325"	72E	R27	BX3A-8C45-A	BX3C-8C45-A	BX3T-8J45-A	BX3U-8J45-A	BM2L-8J45-A	BM2M-8J45-A
	50	20	.058"	.325"	80E	R27	BX3A-8C50-A	BX3C-8C50-A	BX3T-8J50-A	BX3U-8J50-A	BM2L-8J50-A	BM2M-8J50-A
	55	22	.058"	.325"	84E	R27	BX3A-8C55-A	BX3C-8C55-A	BX3T-8J55-A	BX3U-8J55-A		
109,110,111	38	15	.058"	3/8"	56E				DT4T-8Q38-A	DT4U-8Q38-A	DT2L-8Q38-A	DT2M-8Q38-A
115,116,117	40	16	.058"	3/8"	60E	R28.5	DT4A-8C40-A	DT4C-8C40-A				
119,120,219	45	18	.058"	3/8"	64E	R28.5	DT4A-8C45-A	DT4C-8C45-A	DT4T-8Q45-A	DT4U-8Q45-A	DT2L-8Q45-A	DT2M-8Q45-A
PS6000,6800	51	20	.058"	3/8"	72E	R28.5	DT4A-8C51-A	DT4C-8C51-A				
PS540	59	23	.058"	3/8"	80E	R28.5	DT4A-8C59-A	DT4C-8C59-A	DT4T-8Q59-A	DT4U-8Q59-A		
	63	25	.058"	3/8"	84E	R28.5	DT4A-8C63-A	DT4C-8C63-A				
122,123,143	57	23	.058"	3/8"	80E	R34	DR2A-8D57-A		DR2T-8D57-A			
PS9000,9010	62	25	.058"	3/8"	84E	R34	DR2A-8D62-A		DR2T-8Q62-A			
	69	28	.058"	3/8"	92E	R34	DR2A-8D69-A		DR2T-8Q69-A			
	83	33	.058"	3/8"	110E	R34	DR2A-8D83-A		DR2T-8Q83-A			
	90	36	.058"	3/8"	121E	R34	DR2A-8D90-A		DR2T-8Q90-A			

Tanaka

CHAIN SAW MODEL							Guide Bar Part Number					
							Solid Hard nose bar		Replaceable Sprocket nose bar		Laminated Sprocket nose bar	
							Standard	Light	Standard	Light	Standard	Light
ECS415,4000 ECV4501	37	15	.058"	.325"	64E	R24.5	BM3A-8B37-A	BM3C-8B37-A	BM3T-8J37-A	BM3U-8J37-A	BM2L-8J37-A	BM2M-8J37-A
	40	16	.058"	.325"	66E	R27	BM3A-8C40-A	BM3C-8C40-A	BM3T-8J40-A	BM3U-8J40-A	BM2L-8J40-A	BM2M-8J40-A
	42	17	.058"	.325"	68E	R27	BM3A-8C42-A	BM3C-8C42-A	BM3T-8J42-A	BM3U-8J42-A	BM2L-8J40-A	BM2M-8J40-A
	45	18	.058"	.325"	72E	R27	BX3A-8C45-A	BX3C-8C45-A	BX3T-8J45-A	BX3U-8J45-A	BM2L-8J45-A	BM2M-8J45-A
	50	20	.058"	.325"	80E	R27	BX3A-8C50-A	BX3C-8C50-A	BX3T-8J50-A	BX3U-8J50-A	BM2L-8J50-A	BM2M-8J50-A
	55	22	.058"	.325"	84E	R27	BX3A-8C55-A	BX3C-8C55-A	BX3T-8J55-A	BX3U-8J55-A		
ECS505,506 ECS650	40	16	.058"	3/8"	60E	R27.5	XT2A-8C40-A	XT2C-8C40-A	XT2T-8Q40-A	XT2U-8Q40-A	XT2L-8Q40-A	
	45	18	.058"	3/8"	66E	R27.5	XT2A-8C45-A	XT2C-8C45-A	XT2T-8Q45-A	XT2U-8Q45-A	XT2L-8Q45-A	
	50	20	.058"	3/8"	70E	R27.5	XT2A-8C50-A	XT2C-8C50-A	XT2T-8Q50-A	XT2U-8Q50-A	XT2L-8Q50-A	
	61	24	.058"	3/8"	84E	R27.5	XT2A-8C61-A	XT2C-8C61-A	XT2T-8Q61-A	XT2U-8Q61-A	XT2L-8Q61-A	